

commodity	Description	granularity (item)	specifications	packing
Water Sandpaper	Black silicon carbide, even abrasive, very durable.	,400#,,800#,,1200#,2000#	Φ250mm No gum	100pcs/box
Metallographic Sandpaper	Green silicon carbide, even abrasive, wet and dry dual-use.	120#,400#,1000#,2000#,	230×280mm	50pcs/box
		3500#,4000#		
		120#,400#,1000#,2000#,		
		3500#,4000# no Gum		

Name of commodity	description	granularity	Packing
Alumina Grinding Paste	Apply to the non-ferrous metals Metallographic specimen grinding.	W10,	100gram/unit
		W3	
Chromium Oxide Grinding Paste	Apply to Metallographic black metal grinding.	W5	100 gram/unit
		W1	
Diamond Grinding Paste	Apply to high hardness of the metal Metallographic specimen grinding.	W10	5 gram/unit
		W1	
		W0.5	
Alumina Polishing Powder	Apply to the non-ferrous metals Metallographic specimen polishing.	W10	500 gram/bottle
		W7	
		W1	
Chromium Oxide Polishing Powder	Apply to black metal Metallographic specimen polishing.	W10	500gram/bottle
		W5	
		W0.5	
Efficient Diamond Polishing Spray	Precision polishing for all kinds of spare parts of metallographic specimen and instruments. After polishing, can reach desire smooth finish	W7	350ml/bottle
		W2.5	
		W0.5	

material	With Gum specifications	No gum specifications	packing
Velour	Φ200mm	Φ230mm-Φ245mm,	15piece/box
Panne	Φ200mm	Φ230mm-Φ245mm,	15 piece/box
Worsted	Φ200mm	Φ230mm-Φ245mm,	15 piece/box
canvas	Φ200mm	Φ230mm-Φ245mm,	15 piece/box
Woolen Felt	Φ200mm	Φ230mm-Φ245mm,	15 piece/box

Name of commodity	description	packing
Formaldehyde Molding power	Hot Inlay material, white, Application for normal	4kg/ bucket
Ebonite power	Hot Inlay material, black, Application for normal	4kg/ bucket
Cool Inlay King	pink, Application for sample can not be Heated, or without mounting press	Including: 750g/bottle(cool Inlay powder), 500ml/bottle (cool Inlay liquid),Φ30mm cool Inlay molding compound 1set
Crystal King	limpidity, Application for sample can not be Heated, or without mounting press	Including: 1000ml/bottle(cool Inlay liquid),50ml/bottle(Curing agent),Φ30mm molding compound 1 set